

## SwiftCharge Series Portable Box



### • Intelligent

Connectivity: Wi-Fi+Bluetooth  
 Smart mobile App control  
 Scheduled charging  
 1.3-inch OLED Screen shows standby, charging and fault status

### • Flexible Option

Type 2 / Type 1 charging cable  
 4-Stage current adjustable  
 App operation/Plug & Play  
 Compatible with all EV & PHEV models

### • Secure & Safe

AC30mA(CN)/AC30mA+DC6mA(EU)/CCID20(US)  
 Relay-sticking protection  
 Ergonomic and user-friendly enclosure design  
 Over temperature protection  
 Over&Residual current detection

### • Simple Operation

Simple HMI with LED indicators  
 Robust enclosure  
 Easy use

## PRODUCT PARAMETER

Datasheet	Model	BSC-AC0314EN	BSC-AC0714EN
<b>Electrical Specification</b>	Power Supply	1P+N+PE	1P+N+PE
	Rated Voltage	230VAC	230VAC
	Rated Current	8A-10A-13A-16A	16A-20A-24A-32A
	Frequency	50/60Hz	50/60Hz
	Rated Power	3.5KW	7KW
<b>Basic Attributes</b>	Charge Connector	Type 2 cable /Type 1 cable	
	Cable Length	5m (customizable)	
	Enclosure	PC	
<b>Interactive Interface</b>	LEDIndicator	Green/Blue/Red	
	Start Mode	Plug&Play/App	
<b>Communication</b>	WiFi&Bluetooth	Optional	
<b>Safety</b>	RCD	AC30mA +DC 6mA	
	Ingress Protection	IP66	
	Impact Protection	IK08	
	Electrical Protection	Over current protection,Residual current protection,Surge protection, Over/Under voltage protection, Over/Under frequency protection.Overttemperature protection	
	Certification	TUV CE / ETL / FCC / CQC	
	Certification Standard	IEC 62752-2018 IEC61851-21-2:202	
	Warranty	2 years	
<b>Working Environment</b>	Work Temperature	-30°C~+50°C	
	Work Humidity	5%~95%	
	Work Altitude	<2000m	
<b>Package</b>	Product Dimension	297*106.6*53.8mm(H*W*D)	
	Package Dimension	400*320*180mm(L*W*H)	
	Net Weight	4kg	
	Gross Weight	4.3kg	
	ExternalPackage	Handbag/Carton	

