

AltoCharge charger station



Various installation methods Smart and convenient



PRODUCT PARAMETER

Name	DC Charger-30kW/40kW
Power(kW)	30/40kW
Model Number	BSC-DC3001EU/BSC-DC4001EU
Product Name	30-40 kW Wall-Mounted/Floor Mounted DC Charger
Input Voltage(V)	AC380V+15%
Output Voltage(V)	DC150-1000V
Max Input Current(A)	45.58
Max Output Current(A)	100
Voltage regulation accuracy	±0.5%
Steady current accuracy	±1.0%
Efficiency	≥95%
Power Factor	≥0.99
Frequency Range	45-65Hz
Harmonic content	≤5%
Shell Material	Sheet Metal
Dimension (W*D*H)	Wall Mounted :500*260*700 Floor Mounted:500*365*1600
Number of charging ports	1
Cable Length	5m(Customizable)
Application	Indoor/Outdoor
Working Temperature	-20 C C - +50° C
Storage Temperature	-40 C C - +70 C C
Working humidity	5-95%
Working Altitude	<2000m
Degree of Protection	IP54
Cooling way	Air Cooling
Charging method	Card, Scan App, VIN Code
Communication Interface	Standard CAN ,Ethernet, 4G, Wi-Fi
Monitor Interface	OCPP1.6J/OCPP2.0J(Optional)

