

## Warder Home Charger

The stylish Warder Series Home Wallbox is perfect for Type 2/1 EV models. With network connectivity, it offers load balancing and photovoltaic charging features. Ideal for residential use, it combines style and functionality.



### • Intelligen

Connectivity: Wi-Fi+Bluetooth  
Smart mobile App control  
Scheduled charging  
4.3/7 Inches Colors LCD Screen

### • Flexible Option

Type 2 / Type1 charging cable  
16A/32A adjustable output current  
Wall-mount/Floor stand installation  
App operation/RFID authentication/Plug & Play  
Compatible with all EV & PHEV models  
Option to Password / fingerprint

### • Secure & Safe

Type A+DC 6mA  
Relay-sticking protection  
Ergonomic and user-friendly enclosure design  
Over temperature protection  
Over&Residual current detection

### • Simple Operation

Start/Stop charging by RFID card  
Simple HMI with LED indicators  
Robust enclosure  
Easy installation



## PRODUCT PARAMETER

Datasheet	Model	BSC-AC0709EN	BSC-AC1109EN	BSC-AC2209EN
<b>Electrical Specification</b>	Power Supply	1P+N+PE	3P+N+PE	3P+N+PE
	Rated Voltage	230VAC	400VAC	400VAC
	Rated Current	32A	16A	32A
	Frequency	50/60Hz	50/60Hz	50/60Hz
	Rated Power	7KW	11KW	22KW
<b>Basic Attributes</b>	Charge Connector	Type 2 cable / Type 1 cable (11.5KW)		
	Cable Length	5m (customizable)		
	Enclosure	PC		
	Installation	Wall-mount/Pole-mount(Optional)		
<b>Interactive Interface</b>	LEDIndicator	Green/Blue/Red		
	RFID Reader	MifareISO/IEC14443 A		
	4.3'LCD	Optional		
	Start Mode	Plug&Play/RFID card/App		
<b>Communication</b>	Emergency Stop	Yes		
	WiFi&Bluetooth	Optional		
	Fingerprint&Password	Optional		
<b>Safety</b>	RCD	30mA Type A+ 6mA DC sensitive protective device		
	DLB	Optional		
	Ingress Protection	IP65		
	Impact Protection	IK10		
	Electrical Protection	Over current protection,Residual current protection,Surge protection, Over/Under voltage protection, Over/Under frequency protection.Overttemperature protection		
	Certification	CE/FCC / UL		
	Certification Standard	EN IEC61851-1:2019,IEC 61851-1:2017,IEC 61851-21-2:2018		
	Warranty	2 years		
	Work Temperature	-30°C~+50°C		
	Work Humidity	5%-95%		
<b>Working Environment</b>	Work Altitude	<2000m		
	Product Dimension	300*180*120mm(H*W*D)		
	Package Dimension	460*230*250mm(L*W*H)		
<b>Package</b>	Net Weight	3.8kg		
	Gross Weight	4.2kg		
	ExternalPackage	Carton		

